

## 58 Series Premium-line Guestroom Phone



### 58 Series Features:

- **LCD Caller Display** - FSK/DTMF Caller ID system no additional power required (CID Models only)
- **Programmable Guest Service Keys** - Permanent one-touch memory keys
- **Easy Message Retrieval™** - Message Waiting Light, button and Ringer Indicator
- **Speakerphone** (TSD models only) and Hold button with indicators
- **FacePlate Plus™** - full length faceplate and placard faceplate
- **Privacy Guard Redial™** - Last number dialed disappears after a defined time
- **Privacy Guard CID™** - Last inbound number disappears after a defined time (CID Models only)
- **SmartTray™** - stores the handset cord tidily and makes for easier cleaning
- **Auto-Connect™** - Resets the phone to receive incoming calls even when dislodged from the cradle
- **Express Programming** - Supports Remote Programming via Bittel's Express Programming devices
- **SIP (IP) Models** – Full compliance with SIP Protocols and Power-over-Ethernet (PoE)

# Product Datasheet



- Two line auto-select and three-way conference (Two Line phones only)
- Flexible Data Port
- Redial, Flash, Pause, Mute buttons (Flash and Pause time programmable)
- Ringer Volume HI/LOW adjustable
- Speakerphone and Handset volume three level adjustable, and stores the adjustment
- Handset with HAC
- Desk and Wall Mountable



## Available Models:

| Analogue (TDM) Cordless Phones |   |            |
|--------------------------------|---|------------|
| A58-1                          | <b>Single Line Phone (no speaker) for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard</b>                                       |            |
|                                | • No Guest Service Keys   | A58-1-P    |
|                                | • 5 Guest Service Keys  | A58-1-5    |
|                                | • 10 Guest Service Keys   | A58-1-10   |
| A58-1S                         | <b>Single Line Speakerphone for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard</b>   |            |
|                                | • No Guest Service Keys   | A58-1S-P   |
|                                | • 5 Guest Service Keys  | A58-1S-5   |
|                                | • 10 Guest Service Keys   | A58-1S-10  |
| A58-2S                         | <b>Two Line Speakerphone for the Guestroom with Flash, Redial, Hold, Mute, Conference Calling, Cord Tray and Placard</b>                      |            |
|                                | • No Guest Service Keys   | A58-2S-P   |
|                                | • 5 Guest Service Keys  | A58-2S-5   |
|                                | • 10 Guest Service Keys   | A58-2S-10  |
| A58-1D                         | <b>Single Line Caller Display (CID) Phone (no speaker) for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard</b>                  |            |
|                                | • No Guest Service Keys   | A58-1D-P   |
|                                | • 5 Guest Service Keys  | A58-1D-5   |
|                                | • 10 Guest Service Keys   | A58-1D-10  |
| A58-1SD                        | <b>Single Line Caller Display (CID) Speakerphone for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard</b>                        |            |
|                                | • No Guest Service Keys   | A58-1SD-P  |
|                                | • 5 Guest Service Keys  | A58-1SD-5  |
|                                | • 10 Guest Service Keys   | A58-1SD-10 |
| A58-2SD                        | <b>Two Line Caller Display (CID) Speakerphone for the Guestroom with Flash, Redial, Hold, Mute, Conference Calling, Cord Tray and Placard</b> |            |
|                                | • No Guest Service Keys   | A58-2SD-P  |
|                                | • 5 Guest Service Keys  | A58-2SD-5  |
|                                | • 10 Guest Service Keys   | A58-2SD-10 |
| A58-1N                         | <b>Single Line Lobby Phone, One Guest Service Key, and No Dial Pad</b>  |            |

# Product Datasheet



| SIP (IP) Phones |  |             |
|-----------------|--|-------------|
| IP58-1          | <b>Single Line SIP Phone (no speaker) for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard. PoE or Adaptor.</b>                                 |             |
|                 | • 5 Guest Service Keys   | IP58-1-5    |
|                 | • 10 Guest Service Keys  | IP58-1-10   |
| IP58-1S         | <b>Single Line SIP Speakerphone for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard. PoE or Adaptor.</b>                                       |             |
|                 | • 5 Guest Service Keys   | IP58-1S-5   |
|                 | • 10 Guest Service Keys  | IP58-1S-10  |
| IP58-2S         | <b>Two Line SIP Speakerphone for the Guestroom with Flash, Redial, Hold, Conference Calling, Cord Tray and Placard. PoE or Adaptor.</b>                      |             |
|                 | • 5 Guest Service Keys   | IP58-2S-5   |
|                 | • 10 Guest Service Keys  | IP58-2S-10  |
| IP58-1SD        | <b>Single Line SIP Caller Display (CID) Speakerphone for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard. PoE or Adaptor.</b>                  |             |
|                 | • 5 Guest Service Keys   | IP58-1SD-5  |
|                 | • 10 Guest Service Keys  | IP58-1SD-10 |
| IP58-2SD        | <b>Two Line SIP Caller Display (CID) Speakerphone for the Guestroom with Flash, Redial, Hold, Conference Calling, Cord Tray and Placard. PoE or Adaptor.</b> |             |
|                 | • 5 Guest Service Keys   | IP58-2SD-5  |
|                 | • 10 Guest Service Keys  | IP58-2SD-10 |
| IP58-1N         | <b>Single Line SIP (IP) Lobby Phone, One Guest Service Key, and No Dial Pad</b>  |             |

## Specifications:

|                                   |   |
|-----------------------------------|---|
| Phone Dimensions:                 | 24.3cm×16.3cm   |
| Handset cord:                     | 3.66m (Length)  |
| Line cord:                        | 2.0m(Length)  |
| Weight:                           | 1110g   |
| Color:                            | Black / White 2-Tone  |
| Handset:                          | Hearing Aid Compatible (HAC) Handset                                      |
| Dial Character:                   | Standard 12 group (DTMF)  |
| Flash time:                       | 80ms, 100ms, 300ms, 600ms optional, standard is 600ms                     |
| Message Waiting Light Voltage:    | Standard 90~150V DC Customized various MWL card compatible with PBX       |
| Operating Voltage:                | 24 ~ 60V DC   |
| Quality Control:                  | ISO9001, ISO14001   |
| Quality Approval:                 | CCC, FCC, CE, RoHS (FCC Part 15 & 68 compliant)                           |
| One-Touch Memory Key Programming: | Manually Store(Yes) Hand-held Cloner R.P.(Yes) Master Cloner on line(Yes) |
| Box Dimensions:                   | 49×40×26(cm) - 10 Sets /Carton  |

**Bitttel Electronics (EU) Limited**  
 50 Broadway  
 London SW1H 0RG  
 United Kingdom

[www.bitttelcom.eu](http://www.bitttelcom.eu)  
 Tel: +44(0)203 405 1200  
 Fax: +44(0)208 964 5886  
 Email: [europe@bitttelcom.com](mailto:europe@bitttelcom.com)

Solution Partner: